

### 2 Ton Floor Jack

Packing: 1 Order NO.: 904003

YA1642A



### 3-1/2 Ton Floor Jack

Packing: 1 Order NO.: 904004

YA1707



Stock No.	Capacity (tons)	Max Lift Height (inches)	Low Height (inches)	Saddle Size (inches)	Frame Length (inches)	Handle Length (inches)	Weight (lbs)
YA1642A	2	19 1/2	5 1/2	5 1/8	25 3/8	42 1/8	73
YA1707	3 1/2	22	3 3/4	4 1/4	29 7/8	50	103

- Fast acting pump reaches lifting height in less than a pump to allow user to reach a variety of service height situations quickly
- One piece handle for professional users features a foam pad to limit damage to vehicles
- Universal joint release mechanism for smooth action
- Rolled side frames with generous flanges to resist flexing
- Low profile design allows for easy access under vehicles
- Floor Jack used to lift cars and light trucks
- Meets ANSI-PALD standards

### Motorcycle Floor Jack

Packing: 1 Order NO.: 904009

YA1715



### 2 Ton Low-profile Floor Jack

Packing: 1 Order NO.: 904010

YA1716



Stock No.	Capacity (tons)	Max Lift Height (inches)	Low Height (inches)	Saddle Size (inches)	Frame Length (inches)	Handle Length (inches)	Weight (lbs)
YA1716	2	20	3	—	30 1/4	40	97

- 1,500 pound capacity
- Low height of 4 1/2", maximum height of 14 3/4"
- Wide base for extra stability
- Double rubber lined pad provides extra protection to motorcycle while on the jack
- Pull handle assists user to maneuver jack into position
- One foot operation for ease of use
- Safety straps to secure motorcycle to jack
- Self locking safety feature and overload safety valve

- Lift arm is made of ductile iron and is stronger than stamped designs
- 1 pc handle with universal release mechanism
- Fast acting pump brings saddle to service height quickly
- Side plates are flanged for additional strength

### 12 Ton Jack Stands

Packing: 1 Order NO.: 904006

YA512



Stock No.	Capacity (tons)	Low Height (inches)	Maximum Height (inches)
YA512	12 (per pair)	17 1/2	27 1/2

- Counter-weighted pawl serves as a secure locking device to prevent the load from accidentally disengaging
- Sturdy, welded steel construction for superior strength
- One piece, multi-position ductile ratchet bar provides super strength and durability and quick adjustment mechanism that securely locks into desired location

### 1/2 Ton Trans Jack

Packing: 1 Order NO.: 904007

YA714D



Capacity (tons)	Maximum Height (inches)	Saddle Base (inches)	Lifting Head Size (inches)
1/2	69 7/8	8 7/8 x 7 1/8	15 1/2 x 15 1/2
Handle Length (inches)	Chassis Length (inches)	Chassis Width (inches)	Tilt
11	—	33 1/2	12°
Minimum Height (inches)	Exp.Saddle Area (inches)	Jack Size (inches)	Net Weight, lbs. (kg)
33	21 x 21	34 1/8 (L) x 36 1/8 (W)	181 (82.1)

- Crank for precise and easy alignment
- Four adjustment load support arms fit most transmission pan flanges
- Adjustable to 0.030 inches or less
- Foot pedal pump permits hands free operation
- Wide base and four casters for stability